

AMENDMENTS TO THE CLAIMS

Claims 1-32 (Previously Cancelled Without Prejudice or Disclaimer)

Claim 33 (Previously Cancelled Without Prejudice or Disclaimer)

34. (Cancelled Without Prejudice or Disclaimer)

35. (Currently Amended) A transmission apparatus for transmitting a video signal through a transmission path, comprising:

a decoder to decode a compressively coded signal to output picture signals, including a base-band luminous signal and base-band color different signals, and a control signal which is generated based on the compressively coded signal;

an encoder to time-divisionally multiplex the picture signals in a video period and the control signal in a retrace period, thereby to encode the picture signals and the control signal into transmission path signals suited to the transmission path;

an I2C controller to control an I2C (Inter IC control) signal sent to the transmission apparatus from a reception apparatus; and

a CPU to control the I2C controller and the decoder;

wherein the decoder is controlled by the CPU so as to output the picture signals which are displayable in ~~[[a]]~~ [[the]] reception apparatus, on the basis of reception apparatus information included in the I2C signal that is received from the reception apparatus ~~through the I2C controller~~.

Claims 36 and 37 (Previously Cancelled Without Prejudice or Disclaimer)

38. (Currently Amended) A reception apparatus for receiving a video signal through a transmission path, comprising:

a decoder to decode transmission path signal into picture signals, including a base-band luminous signal and base-band color different signals, and a control signal, the transmission path signal is generated by coding the control signal which is generated based on a compressively coded signal, and the video signal so as to be suited to the transmission path, the control signal is time-division-multiplexed in a retrace period;

a ROM table to hold reception apparatus information indicating performance for making the picture signals displayable;

an I2C controller to output the reception apparatus information stored in the ROM table to a transmission apparatus on the basis of an I2C (Inter IC control) signal outputted from the transmission apparatus[[-]] [[;]]

wherein the reception apparatus information is used by the transmission apparatus to output pictures signals which are displayable by the reception apparatus.

39. (Cancelled Without Prejudice or Disclaimer)

40. (Currently Amended) A reception apparatus for receiving a video signal through a transmission path, comprising:

a decoder to decode transmission path signal into picture signals, including a base-band luminous signal and base-band color different signals, and a control signal, the transmission path signal is generated by coding the control signal which is generated based on a compressively coded signal, and the video signal so as to be suited to the transmission path, the control signal is time-division-multiplexed in a retrace period;

a ROM table to hold reception apparatus information indicating performance for making the picture signals displayable;

an I2C controller to output the reception apparatus information stored in the ROM table to a transmission apparatus on the basis of an I2C (Inter IC control) signal outputted from the transmission apparatus; [[and]]

wherein the reception apparatus information is used by the transmission apparatus to output pictures signals which are displayable by the reception apparatus;
and

an image quality controller ~~control~~ to control the image qualities of the picture signals on the basis of the control signal.

41. (Previously Presented) The reception apparatus according to claim 38, wherein the control signal is information indicating at least one of (1) a picture of the picture signals is any of an I picture, a P picture, and a B picture, (2) a picture of the picture

signals is either a picture picked up by progressive scanning or a picture picked up by interlaced scanning, (3) a picture of the picture signals is either a top field or a bottom field picture, (4) a compression ratio of MPEG, and (5) field repeat information of a picture of the picture signals.

42. (Previously Presented) The reception apparatus according to claim 38, wherein the control signal is used for controlling image quality.

43. (Currently Amended) A transmission apparatus which receives a compressively coded signal from a broadcast station for transmitting a video signal to a reception apparatus through a transmission path, comprising:

- a decoder to decode a compressively coded signal to output picture signals, including a base band luminous signal and base band color different signals, and a control signal which is generated based on the compressively coded signal;

- a transmission path encoding circuit for time-division-multiplexing the picture signals in a video period and the control signal in a retrace period, said control signal including information for use in controlling image quality of the picture signals;

- an I2C controller to control an I2C (Inter IC control) signal sent to the transmission apparatus from a reception apparatus; and

- a CPU to control the I2C controller and the decoder;

wherein the decoder is controlled by the CPU so as to output the picture signals which are displayable in ~~[[a]]~~ [[the]] reception apparatus, on the basis of reception apparatus information included in the I2C signal that is received from the reception apparatus through the I2C controller.

44. (Previously Presented) The transmission apparatus according to claim 43, wherein the control signal is information indicating at least one of (1) a picture of the picture signals is any of an I picture, a P picture, and a B picture, (2) a picture of the picture signals is either a picture picked up by progressive scanning or a picture picked up by interlaced scanning, (3) a picture of the picture signals is either a top field or a bottom field picture, (4) a compression ratio of MPEG, and (5) field repeat information of a picture of the picture signals.

45. (Cancelled Without Prejudice or Disclaimer)

46. (Currently Amended) The transmission apparatus of claim [[43]] [[45]], wherein said transmission apparatus is provided by a transmission apparatus set top box (STB).

47. (Currently Amended) The transmission apparatus of claim [[43]] [[45]], wherein said transmission apparatus is a digital camera.

48. (Currently Amended) The transmission apparatus of claim [[43]] [[45]], wherein said transmission apparatus is a notebook computer.

49. (Currently Amended) The transmission apparatus of claim [[43]] [[45]], wherein said transmission apparatus is adapted so that any one of a plurality of different types of television monitors can be connected to said transmission apparatus.

50. (Cancelled Without Prejudice or Disclaimer)

51. (Currently Amended) The transmission apparatus according to claim [[35]] [[50]], wherein the control signal is information indicating at least one of (1) a picture of the picture signals is any of an I picture, a P picture, and a B picture, (2) a picture of the picture signals is either a picture picked up by progressive scanning or a picture picked up by interlaced scanning, (3) a picture of the picture signals is either a top field or a bottom field picture, (4) a compression ratio of MPEG, and (5) field repeat information of a picture of the picture signals.

52. (Currently Amended) The transmission apparatus of claim [[35]] [[50]], wherein said transmission apparatus is provided by a transmission apparatus set top box (STB).

53. (Currently Amended) The transmission apparatus of claim [[35]] [[50]], wherein said transmission apparatus is adapted so that any one of a plurality of different types of television monitors can be connected to said transmission apparatus.